






Orthomat® Ribbed

Ribbed anti-fatigue mat for dry workplaces




- Versatile single layer foam anti-fatigue mat.
- Insulates standing workers against the effects of cold concrete floors.
- Lightweight, so easy to transport and reposition.
- Best suited to dry environments.
- High visibility version available with bright yellow borders.
- Stylish ribbed surface pattern.
- Available in mats and rolls.
- Ideal for lighter industrial use where the user doesn't turn regularly in a static position.
- Fire tested to BS EN 13501-1.



Styles Available



Black



Grey



Grey/Yellow

Parts

Part Number	Size	Colour	Weight (kg)
AL060005	1.2 m x 18.3 m	Grey	51
AL010004	1.2 m x 18.3 m	Black	51
AL060704C	1.2 m x per linear metre	Grey/Yellow	4
AL060004C	0.6 m Linear m	Grey	1.9
AL060004	0.6 m x 18.3 m	Grey	25
AL010003C	0.9 m x per linear metre	Black	2
AL010003	0.9 m x 18.3 m	Black	38
AL060703	0.9 m x 18.3 m	Grey/Yellow	38
AL060702	0.9 m x 1.5 m	Grey/Yellow	3
AL060002	0.9 m x 1.5 m	Grey	3
AL060001	0.6 m x 0.9 m	Grey	1.5
AL060704	1.2 m x 18.3 m	Grey/Yellow	51
AL060003C	0.9 m Linear m	Grey	2
AL060003	0.9 m x 18.3 m	Grey	38
AL010002	0.9 m x 1.5 m	Black	3
AL060701	0.6 m x 0.9 m	Grey/Yellow	1.5
AL010006C	0.6 m x per linear metre	Black	1.7
AL010006	0.6 m x 18.3 m	Black	31
AL060703C	0.9 m x lin. m	Grey/Yellow	2
AL010001	0.6 m x 0.9 m	Black	1.5
AL060005C	1.2 m Linear m	Grey	4
AL010004C	1.2 m x per linear metre	Black	4

Technical Specifications

Material	Open Cell PVC (Foam)
Surface Finish	Ribbed
Product Height	9.5 mm
Size of Safety Border	100 mm
Min. Operating Temperature	0°C
Max. Operating Temperature	+60°C
Environmental Resistance	Suitable for dry indoor environments
Typical Applications	Production lines, Assembly areas, Packing stations, Workbenches
Installation Method	Loose lay
Cleaning Method	Brush/mop the top surface
Fire Tested to	BS EN 13501-1 Class Dfl - s1
COO (Country of Origin)	CN
Guarantee	1 year when used in a dry environment
Adhesive recommended by F.Ball for permanent bond	F44
Tackifier recommended by F.Ball	F41
Adhesive recommended by F.Ball for heavy-duty/wet areas	F74, F81, F84

Additional Information



Orthomat Fire Test BS EN 13501



Orthomat Fire Test EN ISO 11925



Orthomat Fire Test EN ISO 9239

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com