




COBAelite® Bubble

Excellent fatigue relief with superior resilience



- Improve comfort when standing in the workplace.
- Raised surface stimulates blood circulation and foot movement.
- Superior material ensures durability.
- Ramped edges help avoid creating a trip risk.
- Loose lay – can easily be installed in a wide array of workplaces.
- Fire tested to BS EN 13501-1.



Parts

Part Number	Size	Colour	Weight (kg)
SE010010	Special size	Black	
SE010003	0.9 m x 1.2 m	Black	4.5
SE010001	0.6 m x 0.9 m	Black	2

Technical Specifications

Material	PU
Surface Finish	Bubble
Product Height	15 mm
Product Weight	2.5 kg ± 0.2
Min. Operating Temperature	-40°C
Max. Operating Temperature	+80°C
Resistance to Chemicals	PU offers limited resistance to chemicals and oils
Environmental Resistance	Suitable for dry indoor environments
UV Resistance	Yes

Typical Applications	General industrial, Retail
Installation Method	Loose lay
Cleaning Method	Brush down, vacuum clean and wipe with wet cloth
Fire Tested to	BS EN 13501-1 Class Efl - s1
COO (Country of Origin)	DE

Additional Information



COBAelite BS EN 13501 Fire Test



COBAelite EN ISO 11925 Fire Test



COBAelite EN ISO 9239 Fire Test

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com